

ANCHORAGE

ARO BULL TACTICAL



Heavy load double layer textile anchor sling. It is produced in different lengths and it is perfect for high resistance anchoring. The worn indicator allows an immediate inspection of the product. The different internal colouring allows an immediate inspection and it shows at a glance the status of the product. In addition to the standard dimensions possible, on request, custom lengths. Certifications CE EN795/B - EN354 - Polyamide - Maximum load 35kn - Width 25mm - Weight 52 to 270g depending on the length.

*The black color is particularly appreciated for all uses where the equipment must be not very visible (military use, theater and cinema, acrobatic shows, etc ...).



Usage activities

TACTICAL

ITEM CODES

Item	CE EN	Material	▲ (g)	◆ (kN)	Size	Colour	A (mm)	Hole diameter (mm)
280A120N0KK	EN 795/B EN 354	Polyamide	185	35	120	Black	120 cm	/
280A150N0KK	EN 795/B EN 354	Polyamide	230	35	150	Black	150 cm	/
280A180N0KK	EN 795/B EN 354	Polyamide	270	35	180	Black	180 cm	/
280A030N0KK	EN 795/B EN 354	Polyamide	52	35	30	Black	30 cm	/
280A060N0KK	EN 795/B EN 354	Polyamide	95	35	60	Black	60 cm	/
280A080N0KK	EN 795/B EN 354	Polyamide	130	35	80	Black	80 cm	/